

VM-21 シリーズ

仕様書

VM-21G 変換器ソケット



型 名

VM-21G

仕 様

端子ねじサイズ	M3
変換器実装台数	1 台
使用温度	0~50°C
相対湿度	10~90%RH(非凝結)
取付方式	DIN レール、壁取付
外形寸法	W29.5×H72×D30 (mm)
ケース材質 (色)	PPO 樹脂 (黒)
質量	約 50g (本体のみ)
CEマーキング	24VDC 電源仕様のみ

端子配列



端子 No.	VM-21K	VM-21U	VM-21B	VM-21A	VM-21P	VM-21D
1	-24V	/	/	/	IN (A)	IN (F)
2	IN	IN	IN	IN	IN (B)	IN (D/E)
3	COM	COM	COM	COM	IN (C)	IN (C)
4	/	/	/	WAVE	/	IN (A)
5	COM	COM	COM	COM	TP (-)	IN (B) / TP (-)
6	BUF	BUF	BUF	BUF	TP (+)	TP (+)
7	OUT					
8	GND					
9	COM					
10	L +					
11	N -					

端子 No.	VM-21T	VM-21R		VM-21E	VM-21F		
		FK 入力	MS 入力		熱電対	测温抵抗体	mV 信号
1	-24V	-24V	/	IN(+)	IN	A	IN
2	IN	IN		/	/	/	/
3	COM	COM		IN(-)	COM	B	COM
4	/	PULSE		/	/	B	/
5	COM	COM		/	/	/	/
6	BUF	BUF		/	/	/	/
7	OUT						
8	GND						
9	COM						
10	L +						
11	N -						