

Model Code / Additional Specification Code

ZX-3A0

Specification

INPUT

Number of ZARK Nano connection: Up to 16

COMMUNICATION

Communication With ZARK Nano

Radio system: Bluetooth® Low Energy (BLE) 5.0, 2.4 GHz
Maximum communication distance: Approx. 40 m^{*1, *2, *3}

*1 Line-of-sight

*2 The communication distance may vary greatly depending on the installation position and environment.

*3 Check the communication status before installation.

Communication With Machine Dossier

Radio system: IEEE 802.11b/g/n (connection to internet is also required)

POWER SUPPLY

Power supply: 100 to 240 VAC, 50/60 Hz
Circuit breaker: 6 A
Cable: 1.5m / Type B Plug

OPERATING ENVIRONMENT

Temperature: -20 to 60°C
Humidity: 5 to 95% RH (no condensation)

PHYSICAL

Enclosure dimensions(mm): 190 (W) × 280 (H) × 130 (D) (excluding the protrusion and the mounting metal)
214 (W) × 451 (H) × 144 (D) (with the antenna fully extended)
Enclosure material: Plastic
Mass: Approx. 1.6 kg

WARNING

To use wireless devices in countries and regions around the world, it is necessary to obtain a certification under the radio law of the relevant country or region.

The wireless module used in the system can only be used in the country where it has been certified.

If the system is to be used outside Japan, contact the sales office where you purchased the system.

*The items or other information included in this document may change without prior notice.